



www.spotsolar.com



Photovoltaic Modules



Specification Sheet

Models : S-340-72-P

Modules Rating : 340 Watt
 Anodized Aluminum Frame
 Weather Resistant Junction Box
 High Efficiency Crystalline Silicon Solar Cell
 Built-in Bypass Diodes in Junction Box
 Standard IEC 61215, IEC 61730
 TIS 1843-2553, TIS 2580-2555
 ISO 9001:2015, ISO 14001:2015,
 OHSAS 18001:2007 TIS 18001:2011
 25 Years Limited Warranty



Spot solar modules are made with high efficiency Poly Crystalline solar cell and iselectrically matched to minimize losses, for making modules suitablefor commercial as well as domestic application. Spot solar modules have been tested for grid connected as well as stand - alone systems offering high performance and reliability. The solar photovoltaic module is manufactured with crystalline solar cell conforming to the strict requirements to international quality standards. The strings laminated between sheets of ethyl vinyl acetate (EVA) and backsheet. For moisture free protection, UV stability and electrical isolation material are used. Low iron and high transitivity glass is used for strength and high power output. A high quality backsheet (TPT) Provides mechanical protection and electrical insulation up to 1,000 Volt. Each raw material such as EVA, glass and backsheet is procured from the most reliable and proven sources. The laminate are framed with a strong, robust and corrosion resistant aluminum frame with multiple mounting holes for ease of installation as customer's requirement.

Village Power
 Electric Fence Charging
 Telecommunications
 Solar Home System

Recreational
 Telemetry
 Traffic Control Signals
 Water Pumping

Security Lighting
 Battery Maintenance
 Outdoor Lighting
 Solar Grid System

SOLAR POWER TECHNOLOGY CO., LTD.

88 B Building M. 5, T. Chiangraknoi,
 A. Samkhok, Pathumthani 12160, Thailand.
 Tel: +66 (0) 2 156 9166-7 Fax: +66 (0) 2 156 91668



Electrical Properties at Standard Test Condition (STC)

PV Module Model	S-340-72-P
Rated Maximum Power (Pmax)	340 W
Tolerance of Maximum Power	± 5%
Open Circuit Voltage (Voc)	47.6 V
Short Circuit Current (Isc)	9.48 A
Voltage at Pmax (Vmp)	37.7 V
Current at Pmax (Imp)	9.02 A
Efficiency of Module	17.52%


Maximum Use Rate

Maximum System Voltage	1000 V
Maximum Series Fuse	15 A


Mechanical Properties

Dimension	1956 x 992 x 35 mm.
Weight	21.2 Kg.
Frame	Aluminum
Glass	Tempered Glass
Encapsulated Materials	Ethylene Vinyl Acetate (EVA)
Backsheet Materials	Composite Films
Solar Cell	Poly Crystalline Silicon
Junction Box	3 Bypass Diodes
PV Cable	1x4 mm ² Length 1000 mm.

Dimension



I-V Characteristic Curves



Electrical specification are based on measurements performed at standard test conditions (STC) of 1000 W/m² irradiance, air mass 1.5 and cell temperature of 25°C after long-term stabilization. Performance may vary up to 10% from rated power due to temperature operation, spectrum and related effects.

Note: Dimension and electrical specification of the solar modules may change without notice according to the type or size of cells in each lot to used in manufacturing lines.

SOLAR POWER TECHNOLOGY CO., LTD.

88 B Building M. 5, T. Chiangraknoi,
A. Samkhok, Pathumthani 12160, Thailand.
Tel: +66 (0) 2 156 9166-7 Fax: +66 (0) 2 156 91668

